

#### MANUFACTURER:

SaverSystems  
Richmond, IN 47374  
800-860-6327  
Fax: 765-935-4999  
www.chimneysaver.com

#### DESCRIPTION

ChimneySaver Paint "N" Peel Fireplace Cleaner is a water-based cleaning poultice that removes unsightly smoke, soot, creosote and dirt stains from masonry fireplace fronts and hearths. No additional water is needed for application or removal. Simply paint the product on the surface, allow it to dry, and then peel it off.

#### USES

Product can be used to clean most all masonry surfaces both interior/exterior, textured or smooth brick, stone, marble, granite, slate, tile, concrete, mortar and limestone.

**Note:** product may be difficult to remove from extremely textured surfaces or deeply grooved bricks. Always test for compatibility and desired results with your specific surface before proceeding with entire project. Apply product in a small inconspicuous "test" area and allow product to dry completely (**24-48 hours minimum**) before removing. Heavily soiled areas may require multiple applications.

#### ADVANTAGES

- Restores masonry to its original appearance
- Waterless - simply paint on & peel off
- Environmentally friendly - no harsh chemicals
- Works on nearly all masonry surfaces

#### DIRECTIONS FOR USE

**Weather Conditions:** Apply when surface and air temperatures are between 45° F and 95° F.

**Surface Preparation:** Wipe surface with a dry or slightly damp rag to remove dust. Mask off work areas and cover all non-target surfaces with plastic or drop cloths. The use of removable painter's tape is recommended to protect surfaces adjacent to product application, such as fireplace glass doors, fireplace mantles and any trim that abuts the masonry to which product is to be applied. Be sure to protect all surrounding carpet, fabric, metal, wood, and painted surfaces from inadvertent spills and roller splatter, as product may cause stains or damage to non-target surfaces. For best results, surfaces to which product is to be applied should be dust free, dry, and cool to touch before application. **Note:** Do not apply while fireplace is in use.

#### APPLICATION

Stir before use. Tape off area to be cleaned with 2"- wide removable painters tape. Apply a thick, liberal coat, approximately 1/8" – 3/16" thickness using a paint brush and/or a thick nap roller. Apply the product halfway onto the removable painter's tape. **A penny can be used as a thickness gauge. Using the edge with Lincoln's head, stick penny into applied material. The material should be thick enough to reach Lincoln's forehead (see diagram 1).**



Be sure to maintain the recommended thickness across the entire surface area to be coated and near the edges of your project. Ensuring an even application will help the product peel off easily and uniformly when dry. Peel off the painter's tape with dried material applied onto the tape for easier removal. For areas that are more heavily soiled, agitation with a stiff nylon bristle scrub brush may be required to help the product work deeper into the surface. Once surface has been agitated, re-coat to be sure a thick, even application of product remains on surface. On extremely porous surfaces or in extremely dry conditions, it may be beneficial to lightly mist the surface with water, agitate with a soft bristle brush and blot dry with clean rags just prior to application to help prevent product from drying out too quickly.

**Drying time:** At 1/8"-3/16" thickness, product will take a **minimum of 24-48 hours** to dry completely, depending on environmental conditions.

**Removal of Dry Product:** Product must be completely dry before removing. Starting at an edge, pull the dry film off slowly at an angle with both hands. Be careful not to tear the coating as this may make it more difficult to remove. Product that does not pull off in a continuous sheet indicates the dried film is too thin to peel easily. Re-coat over the thinly applied material with a thick coat of product, let dry completely and re-peel. Once film is completely removed, fireplace can be put back in use.

**Coverage:** When applied at 1/8" - 3/16" thickness, product will cover 20 - 40 sq. ft. per gallon depending on the texture and density of the surface.

#### CLEAN UP

Wipe excess material off of tools. Tools may then be cleaned with soap and water. Dispose of dried coating in accordance with local regulations for non-hazardous solid waste. Absorb small spills with inert material and dispose of according to local regulations. Rinse spill area with water.

#### CAUTIONS

**Keep out of reach of children.** Do not take internally. Close container after each use. Do not reuse containers. The use of protective gloves and eye wear is recommended to avoid contact with skin and eyes.

#### FIRST AID

**If swallowed:** Rinse mouth. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Obtain emergency medical attention. **For skin contact:** Wipe off excess material and wash exposed skin with mild soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. **For eye contact:** Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately. For additional information for this product, consult the Safety Data Sheet available at [www.chimneysaver.com](http://www.chimneysaver.com).

#### LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to the results is offered, expressed or implied. SaverSystems warrants this product to be free from defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product has been applied. This warranty does not include the cost of labor for application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

#### PACKAGING

Available in one-gallon recyclable plastic containers.

#### TRANSPORT AND HANDLING

ChimneySaver Paint "N" Peel fireplace cleaner is not considered hazardous under Department of Transportation (DOT) regulations. Store in a cool, dry, well ventilated place. Do not stack pallets. **Keep from freezing.**

#### PHYSICAL PROPERTIES

COLOR . . . . . Light gray, thick paste  
COMPOSITION. . . . . Proprietary blend of water miscible polymers and surfactants  
WEIGHT . . . . . (8.5 lbs/gallon)  
VOC CONTENT (ASTM D 6886) . . . . . < 41 g/L  
SHELF LIFE . . . . . 24 months when unopened  
FLASH POINT . . . . . None  
FREEZE/THAW STABILITY . . . . . N